

ODE-3-110070-1012-01

Optidrive E3 Single Phase VFD Datasheet

0,37 kW (0,5 HP), 7 A, 110-115 V, 1PH

Variadores de frecuencia



Input Ratings

Supply Voltage	110-115 V
Input Phases	1
Supply Current Continuous	8,5 A
Supply Fuse or MCB (Type B)	16 A

Output Ratings

Motor Output Rating	0,37 kW (0,5 HP)
Output Voltage	0 – Supply Voltage
Output Current	7 A

Cable Information

Max Supply Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Sin transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	

Dimensions

Size	1
Height	173 mm (6,81 in)
Width	83 mm (3,27 in)
Depth	123 mm (4,84 in)
Weight	1 kg (2,2 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	165 mm (6,5 in)
Width	125 mm (4,92 in)
Depth	235 mm (9,25 in)
Weight	1,2 kg (2,65 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

