

ODE-3-320240-3042

Optidrive E3 VFD Datasheet

5,5 kW (7,5 HP), 24 A, 200-240 V, 3PH

Variadores de frecuencia



Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	26,4 A
Supply Fuse or MCB (Type B)	40 A

Output Ratings

Motor Output Rating	5,5 kW (7,5 HP)
Output Voltage	0 – Supply Voltage
Output Current	24 A

Cable Information

Max Supply Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	

Dimensions

Size	3
Height	261 mm (10,28 in)
Width	131 mm (5,16 in)
Depth	175 mm (6,89 in)
Weight	3,2 kg (7,05 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	254 mm (10 in)
Width	162 mm (6,38 in)
Depth	315 mm (12,4 in)
Weight	3,5 kg (7,72 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

