

# ODE-3-420300-3042

Optidrive E3 VFD Datasheet

**7,5 kW (10 HP), 30 A, 200-240 V, 3PH**

Variadores de frecuencia



## Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	33,3 A
Supply Fuse or MCB (Type B)	40 A

## Output Ratings

Motor Output Rating	7,5 kW (10 HP)
Output Voltage	0 – Supply Voltage
Output Current	30 A

## Cable Information

Max Supply Cable Size	16 mm <sup>2</sup> (0,02 sq in)
Max Motor Cable Size	16 mm <sup>2</sup> (0,02 sq in)
Max Motor Cable Length	100 m (328 ft)

## Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	


## Dimensions

Size	4
Height	420 mm (16,54 in)
Width	171 mm (6,73 in)
Depth	212 mm (8,35 in)
Weight	9,1 kg (20,06 lbs)
Fixings	4 x M8

## Packaged Dimensions

Height	340 mm (13,39 in)
Width	282 mm (11,1 in)
Depth	560 mm (22,05 in)
Weight	10,5 kg (23,15 lbs)



 **Buy this drive or get more information**  
Find your local sales partner on  
[invertekdrives.com](http://invertekdrives.com)

 **Invertek**  
Drives.com