

ODV-3-220070-1F12-MN

Optidrive Eco VFD Datasheet

1,5 kW (2 HP), 7 A, 200-240 V, 1-3PH

Variadores de frecuencia con filtro CEM y
Pantalla TFT Pantalla



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	15,2 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	1,5 kW (2 HP)
Output Voltage	0 – Supply Voltage
Output Current	7 A

Cable Information

Max Supply Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	CEM interno
Brake Transistor	Sin transistor de freno
Enclosure	IP20
Display	Pantalla TFT
PCB Coating	Estándar

Dimensions

Size	2
Height	221 mm (8,7 in)
Width	110 mm (4,33 in)
Depth	185 mm (7,28 in)
Weight	1,8 kg (3,97 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	265 mm (10,43 in)
Width	145 mm (5,71 in)
Depth	230 mm (9,06 in)
Weight	1,9 kg (4,19 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
invertekdrives.com

 **Invertek**
Drives.com